An INTELLIGENT COMPRESSED AIR Product

Safety Air Nozzles

Safety Air Nozzles



Model 1001 1/8 NPT female Material: Brass

Model 1002 1/4 NPT female Material: Brass

Model 1002SS 1/4 NPT female Material: Type 303 Stainless Steel

Model 1003 3/8 NPT female Material: Brass

Send in your air nozzle

for the Award Winning



Service

We will test your existing product for air use, noise and force. We'll compare it to our Intelligent Compressed Air® products and provide a full report to help improve your process.


Contact an **Application Engineer** at 1-800-903-9247.

Model 1001, 1002, 1002SS and 1003 Safety Air Nozzles


Safety Air Nozzles eject a small amount of compressed air 360° around the outer ring that combines with the air ejected from the center hole to produce a high volume, high velocity blast of air. The slotted end allows air to vent safely should the nozzle end be blocked.

Air Consumption			For	Sound Level	
Model	SCFM	SLPM	Ozs	Grams	dBA
1001	10	283	9	255	78
1002	17	481	16	454	80
1002SS	17	481	16	454	80
1003	18	509	18	510	83

* Force measured at 12" (305mm) from target Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR)



Dimensions		Α	В	C	D	
Model				Hex	Inlet	
1001	in	1.19	0.38	1/2	1/8 NPT	
1001	mm	30	10	13		
1002	in	1.44	0.50	5/8	1/4	
100255	mm	37	13	16	NPT	
1003	in	1.65	0.63	3/4	3/8	
1003	mm	42	16	19	NPT	



Model		E	F	G	Н
1001	in	1.1	2.1	4.1	6.0
1001	mm	28	53	104	152
1002	in	1.3	2.3	4.4	6.5
1002SS	mm	33	58	112	165
1003	in	1.3	2.4	4.7	7.0
1003	mm	33	61	119	178

Adjustable Air Nozzles



Model 1009 1/8 NPT male Material: Aluminum

Model 1009SS 1/8 NPT male Material: Type 303 Stainless Steel



Adjustable Air Nozzles are perfect for a variety of blowoff applications.

Model 1009 and 1009SS **Adjustable Air Nozzles**

Adjustable Air Nozzles are suitable for a wide variety of blowoff applications. The design allows you to "tune in" the force and flow to the application requirements, thereby minimizing air consumption. A micrometer-like dial indicates the gap setting. A set screw in the end can be tightened so the air nozzle holds the setting.

Air Consumption		For	Sound Level	
SCFM	SLPM	Ozs	Grams	dBA
13	368	12	340	79

Force measured at 12" (305mm) from target with a .008" (0.20mm) factory setting Sound level measured at 3' (914mm) All measurements taken at 80 PSIG (5.5 BAR)

